

AMENDMENTS TO THE CLAIMS

1. (Currently Amended): A safety indwelling needle, comprised of a metallic inner needle which pierces a skin of a patient and reaches a blood vessel; and a soft outer needle which is located outside the inner needle and places within the blood vessel, comprising:
- a holder sleeve having a retracting mechanism which can hold the inner needle after a puncture, from a proximal end to a distal end thereof and does not hold the outer needle, characterized in that
 - the retracting mechanism includes: an urging means for urging the inner needle to a side opposite to the outer needle with respect to an axial direction of the holder sleeve; an actuator which moves together with the inner needle when it is withdrawn and has a puncture position retainer for keeping the inner and outer needles ready for the puncture and an inner needle retraction actuating portion for allowing for the retraction actuation of the inner needle; and a slit formed in the holder sleeve for assuring a movement path of the actuator,
 - the urging means is a biasing element that applies a biasing force to the actuator,
 - ~~the inner needle retraction actuating portion is projected outward of the holder sleeve through the slit,~~
 - the puncture position retainer has a puncture position engagement portion whereby the actuator is engaged with the holder sleeve at a position on an outer needle side,
 - the inner needle retraction actuating portion has an actuating portion for releasing the actuator from an engaged state of the puncture position engagement portion into an urged state by the urging means; and
 - the retracting mechanism has an actuating portion housing for

enclosing the inner needle retraction actuating portion and preventing the inner needle retraction actuating portion from coming into contact with a hand after retraction of the inner needle.

2. (Original) The safety indwelling needle according to Claim 1, wherein the actuator housing portion is constructed of wall portions formed standing at both sides of the slit in the holder sleeve on the side opposite to the outer needle and a protective cover portion joining the edges of the wall portions.
3. (Original) The safety indwelling needle according to Claim 2, wherein the protective cover portion is formed so as to function as a tail plug for closing an opening of the holder sleeve on the side opposite to the outer needle.
4. (Previously Amended) The safety indwelling needle according to Claim 1, wherein the retracting mechanism has a stopper for arresting the inner needle moved to the side of the holder sleeve opposite to the outer needle, the stopper includes arrest engagements for stopping the inner needle stored in the holder sleeve relative to the holder sleeve.
5. (Previously Amended) The safety indwelling needle according to Claim 1, wherein, on the outer needle side of the holder sleeve, a grip portion to be held when the outer and inner needles are punctured into the skin of the patient is formed at a position other than a position where the actuating portion of the actuator is arranged.
6. (Previously Amended) The safety indwelling needle according to Claim 1, further comprising a cap which covers the outer and inner needles while keeping them ready for puncture and disables the function of the actuating portion.

puncture position engagement portion into an urged state by the coil spring,

the actuator housing portion is constructed of wall portions standing at both sides of the slit in the holder sleeve on the side opposite to the outer needle and a protective cover portion joining the edges of the wall portions, the protective cover portion being formed so as to function as a tail plug for closing an opening of the holder sleeve on the side opposite to the outer needle, and

the stopper includes arrest engagements for stopping the inner needle held in the holder sleeve relative to the holder sleeve.

8. (Previously Added) The safety indwelling needle according to Claim 1, wherein the puncture position retainer is projected outward of holder sleeve through the slit, and

the puncture position engagement portion is engaged with a engagement window provided on outer surface of the holder sleeve.

9. (Previously Added) The safety indwelling needle according to Claim 7, wherein the puncture position retainer is projected outward of holder sleeve through the slit, and

the puncture position engagement portion is engaged with an engagement window provided on an outer surface of the holder sleeve.

10. (Previously Added) The safety indwelling needle according to Claim 1, wherein the biasing element is in a compressed state when the inner needle is retracted.

11. (Previously Added) The safety indwelling needle according to Claim 7, wherein the coil spring is in a compressed state when the inner needle is retracted.